

# Certified Pre-Owned Products

## Comparison Guide

### Certified Pre-Owned Bronchoscopes

Model	HD or Standard Definition	Insertion Tube Outer Diameter (mm)	Working Channel Diameter (mm)	Bending Up/Down	Bending Left/Right	Working Length (cm)	Field Of View	Depth Of Field (mm)	Water Jet?	Platform Compatibility	Additional Features
BF-1TH190	High Def	6.2	2.8	180°/130°	120° R/L	60	120°	3-100	No	CV-190, CV-1500	
BF-H190	High Def	5.5	2.0	210°/130°	120° R/L	60	120°	3-100	No	CV-190, CV-1500	
BF-MP190F	STD DEF	3.7	1.7	210°/130°	120° R/L	60	90°	2-50	No	CV-190, CV-1500	
BF-P190	STD DEF	4.2	2.0	210°/130°	120° R/L	60	110°	2-50	No	CV-190, CV-1500	
BF-Q190	STD DEF	4.8	2.0	210°/130°	120° R/L	60	120°	3-100	No	CV-190, CV-1500	
BF-UC190F	STD DEF	6.6	2.2	160°/70°	0° R/L	60	80°	2-50	No	CV-190, CLV-190, CV-180, CLV-180, EU-ME1, EU-ME2, EU-ME2 PREMIER PLUS, *ARIETTA 850/850 AT (*software compatibilities may vary. Please speak with your Endoscopy Account Manager for processor directed questions).	Endoscopic Ultrasound
BF-XP190	STD DEF	3.1	1.2	210°/130°	120° R/L	60	110°	2-50	No	CV-190, CV-1500	
BF-XT190	STD DEF	6.3	3.2	180°/130°	120° R/L	60	110°	2-50	No	CV-190, CV-1500	

### Certified Pre-Owned Colonoscopes

Model	HD or Standard Definition	Insertion Tube Outer Diameter (mm)	Distal End Outer Diameter (mm)	Working Channel Diameter (mm)	Bending Up/Down	Bending Left/Right	Working Length (cm)	Field Of View	Depth Of Field (mm)	Water Jet?	Platform Compatibility	Additional Features
CF-HQ190I	HD	12.8	13.2	3.7	180°/180°	160°/160°	133	170°	Near: 2-6 Normal: 5-100	Yes	CV-190 & CV-1500	RIT, Dual Focus, NBI Technology, Waterproof One-touch Connector
CF-HQ190L	HD	12.8	13.2	3.7	180°/180°	160°/160°	168	170°	Near: 2-6 Normal: 5-100	Yes	CV-190 & CV-1500	RIT, Dual Focus, NBI Technology, Waterproof One-touch Connector
PCF-H190TL	STD DEF	10.5	9.8	3.2	210°/180°	160°/160°	168	140°	Normal: 2-100	Yes	CV-190 & CV-1500	Variable Stiffness & High Force Transmission (no Passive Bending), NBI Technology, Waterproof One-touch Connector
PCF-HQ190L	HD	12	11.8	3.2	180°/180°	160°/160°	168	170°	Near: 2-6 Normal: 5-100	Yes	CV-190 & CV-1500	RIT, Dual Focus, NBI Technology, Waterproof One-touch Connector
PCF-PH190L	STD DEF	9.5	9.7	3.2	180°/180°	160°/160°	168	140°	Normal: 2-100	No	CV-190 & CV-1500	Passive Bending & High Force Transmission (no Variable Stiffness), NBI Technology, Waterproof One-touch connector

### Certified Pre-Owned Gastrosopes

Model	HD or Standard Definition	Insertion Tube Outer Diameter (mm)	Distal End Outer Diameter (mm)	Working Channel Diameter (mm)	Bending Up/Down	Bending Left/Right	Working Length (cm)	Field Of View	Depth Of Field (mm)	Water Jet?	Platform Compatibility	Additional Features
GIF-1TH190	HDTV	10.9	10.0	3.7	210°/90°	100°/100°	103	140°	Normal: 2-100	Yes	CV-190	NBI Technology; Waterproof One-touch Connector
GIF-H190	HDTV	9.2	9.2	2.8	210°/90°	100°/100°	103	140°	Normal: 5-100	Yes	CV-190, CV-1500	NBI Technology; Waterproof One-touch Connector
GIF-HQ190	HDTV	9.9	9.9	2.8	210°/90°	100°/100°	103	140°	Near: 2-6 Normal: 5-100	Yes	CV-190, CV-1500	Dual Focus; NBI Technology; Waterproof One-touch Connector
GIF-XP190N	HDTV	5.8	5.4	2.2	210°/90°	100°/100°	110	140°	Normal: 3-100	No	CV-190, CV-1500	NBI Technology; Waterproof One-touch Connector

# Certified Pre-Owned Products

## Comparison Guide

### Certified Pre-Owned EUS Scopes

Model	HD or Standard Definition	Insertion Tube Outer Diameter (mm)	Working Channel Diameter (mm)	Bending Up/Down	Bending Left/Right	Working Length (cm)	Field Of View	Depth Of Field (mm)	Water Jet?	Platform Compatibility	Additional Features
GF-UCT180	STD DEF	12.6	3.7	130°/90°	90°/90°	125	100°	3-100	Yes	CV-180, CV-190, EU-ME1, EU-ME2/ PREMIER PLUS, ProSound F75, ARIETTA 850/AT	

### Certified Pre-Owned Duodenoscopes

Model	HD or Standard Definition	Insertion Tube Outer Diameter (mm)	Distal End Outer Diameter (mm)	Working Channel Diameter (mm)	Bending Up/Down	Bending Left/Right	Working Length (cm)	Field Of View	Depth Of Field (mm)	Water Jet?	Platform Compatibility	Additional Features
TJF-Q190V	HDTV	11.3	13.5	4.2	210°/90°	110°/90°	124	100°/15° (backward)	Normal: 5-60	No	CV-190, CV-1500	Single-use distal cover; Guidewire locking capability; NBI™ Technology; Waterproof one-touch connector; High force transmission

### Certified Pre-Owned Electronics

Model	HD or Standard Definition	Platform Compatibility	Additional Features
OEP-6	HD (1080p)	CV-190, CV-1500, OTV-S400, OTV-S300, OTV-S190, EU-ME2	379 dpi, 3G SDI compatible
OEV-262H	HD (1080p)	CV-170, CV-180, CV-190, CV-1500	
OEV321UH	UHD (4K)	CV-190, CV-1500, OTV-S200	Clone Out, A.I.M.E.
OFFP-2		CV-190, CV-1500	
UCR		Gastrointestinal Videoscope/Fiberscope, Duodenovideoscope/Fiberscope, Small Intestinal Videoscope, Colonovideoscope/Fiberscope, Sigmoidovideoscope, and Gastroideoscope within the EVIS EXERA 180 series, EVIS EXERA 190 series, EVIS X1 1100 series	

### Certified Pre-Owned Electronics (Continued)

Model	Light Source	Digital Imaging Processing	Iris	Pre-Freeze	Electronic Zoom	Video Outputs	Internal Memory	USB Memory	Magnetic Endoscopic Imaging	Scope Connection
CLV-90	Xenon Light Bulb									One Touch, Connector
CV-190		Structure Enhancement	Auto/Average/Peak	Yes	1-1.5x	HD-SDI, SD-SDI, DVI, RGB-Sync, YPbPr, VBS Composite, Y/C	Yes	up to 2048 images	ScopeGuide™ Technology	

Please refer to instruction manuals for more detailed specification information.

Specifications, design and accessories are subject to change without any notice or obligation on the part of the manufacturer.

Olympus is a registered trademark of Olympus Corporation, Olympus America Inc., and/or their affiliates. | Medical devices listed may not be available for sale in all countries.



**OLYMPUS AMERICA INC.**

3500 Corporate Parkway, PO BOX 610, Center Valley, PA 18034

[www.medical.olympusamerica.com](http://www.medical.olympusamerica.com)

For more information, contact your Olympus sales representative, or call 800-548-5515.

©2026 Olympus America Inc. All rights reserved.

Printed in USA OAIG10426QRG60609